



2.5-inch U.2 NVMe SSD
7.68TB, 3.84TB, 1.92TB and 960GB

Features & Benefits

- PCIe Gen 3, x4 interface and NVMe™ 1.3 compliant with in-box driver support
- Industry-standard 2.5-inch U.2 small form factor for high serviceability in a slim 7mm package
- Capacities up to 7.68TB¹
- Optimized for read-intensive & mixed-use workloads
- Up to 176K IOPS (70/30 random mixed workload)
- 65% less power consumption compared to 25W PCIe SSD solutions
- Hot Swap/Hot Plug support with data-loss protection
- NVMe MI 1.0 Management Interface Support
- MTBF rating of 2 million hours
- Instant Secure Erase (ISE) with AES-256 encryption

Specialized for the Following Applications

- Cloud and hyperscale storage
- Software Defined Storage
- File, Block and Object Storage applications
- Direct-attached Storage (DAS)
- Hyper-converged Infrastructure
- NoSQL databases
- Content Delivery Network (CDN)
- Virtualization
- OLAP
- File/web servers
- Media streaming & VoD

Economies of Scale Propel Cloud Storage

Next generation cloud data centers are now deploying NVMe SSD storage as a core component, replacing the slower legacy SATA interface. The Ultrastar DC SN630 NVMe SSD is built on Western Digital's in-house controller and firmware technology and utilizes our own 64-layer BiCS3 3D NAND, which allows Western Digital to tightly control all design aspects and consistently deliver low latency and high performance. This essential NVMe offering provides twice the maximum capacity per slot and more capacity choices than our prior generation, up to 7.68TB.

Cloud services are revolutionizing how companies think about data storage by transitioning from fixed-cost IT infrastructure to variable cost models. As more business services move to the cloud to reap the benefits of the "pay-as-you-go" model, the demands on cloud service providers to scale increase exponentially. Finding ways to maximize and streamline storage by running concurrent workloads across the storage infrastructure has become essential. Furthermore, cloud storage services must offer high availability and consistent I/O performance to be delivered 24/7, 365 days a year. Ultrastar® DC SN630 NVMe™ SSDs help customers meet these rigorous requirements at a viable \$/GB.

Ultrastar DC SN630 SSDs Increase Productivity and Lower TCO

SATA SSDs have long been used in data centers and cloud storage. But as capacity needs grow, along with the necessity to access data with minimal latency, the adequacy of the interface bandwidth between the host and the drive comes under scrutiny. The SATA (6Gb/s) interface constrains performance of most SSDs and introduces latency compared to NVMe SSDs. Utilizing higher capacity points with fast, low latency NVMe allows data center architects to reduce the number of servers deployed while still handling more users and providing more services per server. Server reduction, in turn, reduces the number of "per-core" software licensing fees required resulting in even lower TCO.

Highly Reliable Storage Innovation

Utilizing the industry standard NVMe command protocol that lowers latency and improves bandwidth, Ultrastar DC SN630 SSDs enable a cost-effective transition to next-generation storage platforms.

Available in the 2.5-inch U.2 small form factor with a slim 7mm profile, typical power consumption under 10.75W, and hot-swap capability, Ultrastar DC SN630 NVMe SSDs simplify large-scale deployment in the data center. This results in efficient workload utilization, a lower thermal profile compared to 25W PCIe SSDs, and improved TCO.

Ultrastar DC SN630 SSDs protect your data by providing data protection, proprietary wear levelling algorithms, and power loss protection required in a demanding enterprise environment. By leveraging Western Digital's history of providing world class enterprise storage solutions, manufacturing excellence, and commitment to reliability leadership, Ultrastar DC SN630 SSDs enable data center customers to innovate with minimal risk, backed with a 5-year limited warranty.

Options to Simplify Data Security

Compliance and privacy requirements drive the need for increased data security. Ultrastar DC SN630 models with Instant Secure Erase (ISE) provide peace of mind by using behind-the-scenes encryption keys to expedite drive redeployment and retirement.

Secure Firmware downloads with RSA authentication ensure that the drive runs authentic Western Digital firmware only.

Specifications

Model	VRI			
Configuration				
Capacity ¹	960GB	1,920GB	3,840GB	7,680GB
Form Factor	U.2 2.5-inch drive			
Interface	PCIe Gen 3.0 x4 (Compliant to NVMe™ 1.3)			
Endurance (Drive writes per day, DW/D) ²	0.8			
Flash Memory Technology	WDC BiCS3 3D TLC NAND			
Performance³ (Specified at 10.75W Average)				
Sequential Read, (max MiB/s, 128KiB BS, QD128)	2,770	2,750	2,580	2,620
Sequential Write, (max MiB/s, 128KiB BS, QD128)	970	1,270	1,230	1,290
Random Read (max IOPS, 4KiB BS, QD128)	277,220	348,590	329,020	363,750
Random Write (max IOPS, 4KiB BS, QD128)	46,410	51,460	55,820	54,490
Random Mix R70/W30 (max IOPS, 4KiB BS, QD128)	114,520	170,450	165,490	176,100
Latency Distribution (Specified at 10.75W Average)				
Random Read Latency (4KiB BS, QD1, 99.99%) (µs)	120	180	230	230
Reliability				
Uncorrectable Bit Error Rate (UBER)	1 in 10 ¹⁷			
EOL Data Retention	3 months at 40° C			
MTBF	2 million hours			
Annualized Failure Rate (AFR) ⁴	0.44%			
Limited Warranty ⁵	5 years			
Electrical				
Requirement (DC +/- 10%)	12V			
Operating Power States (W, average)	10.75 & 8.75			
Idle (W, average)	5.6			
Environmental				
Operating Temperature ⁶	0° C to 70° C			
Non-operating Temperature	-40° C to 85° C			
Physical Measurements				
Width (mm)	69.85 +/-0.25			
Length (mm, max)	100.45			
Weight (g, max)	95			
z-height (mm)	7.00 +0.2/-0.5			

Feature	Part Number	Model Number	Capacity	Endurance
Instant Secure Erase	OTS1617	WUS3BA196C7P3E3	960GB	0.8 DW/D
	OTS1618	WUS3BA119C7P3E3	1,920GB	0.8 DW/D
	OTS1619	WUS3BA138C7P3E3	3,840GB	0.8 DW/D
	OTS1620	WUS3BA176C7P3E3	7,680GB	0.8 DW/D

¹ One gigabyte (GB) is equal to 1,000MB (one billion bytes) and one terabyte (TB) is equal to 1,000GB (one trillion bytes) when referring to solid-state capacity. Accessible capacity will vary from the stated capacity due to formatting and partitioning of the drive, the computer's operating system, and other factors.

² Endurance rating based on 100% 4KiB Random Write workload.

³ Performance will vary by capacity point or with the changes in useable capacity. Consult product manual for further details. All performance measurements are in full sustained mode and are peak values. Subject to change. 1MiB= 1,048,576 bytes or 2²⁰. 1KiB= 1,024 bytes or 2¹⁰. Source: Actuals_vs_measured.xlsx. Data reflects actual measured... round to 10ths.

⁴ MTBF and AFR targets are based on a sample population and are estimated by statistical measurement and acceleration algorithms under median operating conditions. MTBF and AFR rating do not predict an individual drive's reliability and do not constitute a warranty.

⁵ The lesser of 5 years from the date of manufacture of the product or the date on which the product's relevant endurance thresholds set forth in the product specifications are reached.

⁶ Internal temperature sensor reading.

Western Digital

5601 Great Oaks Parkway
San Jose, CA 95119, USA
US (Toll-Free): 800.801.4618
International: 408.717.6000

www.westerndigital.com

© 2017-19 Western Digital Corporation or its affiliates. All rights reserved. Produced 2/17. Rev. 3/19. Western Digital, the Western Digital logo, iNAND, and Ultrastar are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the U.S. and/or other countries. All other marks are the property of the respective owners. References in this publication to Western Digital products, programs, or services do not imply that they will be made available in all countries. Product specifications provided are sample specifications that are subject to change and do not constitute a warranty. Please visit the Support section of our website, www.westerndigital.com/support, for additional information on product specifications. Pictures shown may vary from actual products.